

### Airless hadice

Stříkací hadice v různém provedení pracovního tlaku. Kombinací délky hadice s různými koncovkami je možné provést individuálně na přání zákazníka.



### Technická specifikace

Objednací číslo	Popis
	1,5 m 1/8" - 260 Bar - 1/4" NPS (F) x (M) - SS
	1,5 m 3/16" - 250 Bar - 1/4" NPS (F) x (M)
	1,5 m - 3/16" - 250 Bar - 1M16x1,5mm (F) x (M)
	1,5 m - 1/4" - 260 Bar - 1/4" NPS (F) x (M)
	1,5 m - 1/4" - 260 Bar - 1/4" NPS (F) x 3/8" (M)
	1,5 m - 1/4" - 260 Bar - M16x1,5mm (F) x (M)
PA-14BL-1,5N	1 x ocelový oplet - 3/16" - 350 Bar 1/4" NPS (F) x (M)
PA-14BL-1,5M	1 x ocelový oplet - 3/16" - 350 Bar M16x1,5mm (F) x (M)

### Hadice s dvojnásobným textilním opletem a koncovkami

Objednací číslo	Popis
<b>3/16" (NW4/5) 250 bar</b>	
KX-23GY-7,5N	7,5 m - 1/4" NPS
KX-23GY-7,5M	7,5 m - M16x1,5mm
KX-23GY-10N	10 m - 1/4" NPS
KX-23GY-10M	10 m - M16x1,5mm
<b>1/4" (NW6) 260 bar</b>	
KX-24GY-5N	5 m - 1/4" NPS
KX-24GY-5M	5 m - M16x1,5
KX-24GY-7,5N	7,5 m - 1/4" NPS
KX-24GY-7,5M	7,5 m - M16x1,5
KX-24GY-10N	10 m - 1/4" NPS

KX-24GY-10M	10 m – M16x1,5
KX-24GY-15N	15 m – 1/4" NPS
KX-24GY-15M	15 m – M16x1,5
KX-24GY-20N	20 m – 1/4" NPS
KX-24GY-20M	20 m – M16x1,5
KX-24GY-25N	25 m – 1/4" NPS
KX-24GY-25M	25 m – M16x1,5

### **3/8" (NW10) 260 bar**

KX-26GY-15N	15 m – 3/8" NPS
KX-26GY-15M	15 m – M16x1,5mm
KX-26GY-20N	20 m – 3/8" NPS
KX-26GY-20M	20 m – M16x1,5mm
KX-26GY-25N	25 m – 3/8" NPS
KX-26GY-25M	25 m – M16x1,5mm
KX-26GY-30N	30 m – 3/8" NPS
KX-26GY-30M	30 m – M16x1,5mm

### **Hadice s ocelovým opletem a koncovkami**

#### **3/16" (NW4/5) 350 Bar**

PA-13BL-7,5N	7,5 m – 1/4" NPS
PA-13BL-7,5M	7,5 m – M16x1,5mm

#### **1/4" (NW6) 325 Bar**

PA-14BL-10N	10 m – 1/4" NPS
PA-14BL-10M	10 m – M16x1,5
PA-14BL-15N	15 m – 1/4" NPS
PA-14BL-15M	15 m – M16x1,5
PA-14BL-20N	20 m – 1/4" NPS
PA-14BL-20M	20 m – M16x1,5
PA-14BL-25N	25 m – 1/4" NPS
PA-14BL-25M	25 m – M16x1,5

#### **3/8" (NW10) 250 Bar**

PA-16BL-15N	15 m – 3/8" NPS
PA-16BL-15M	15 m – M16x1,5mm
PA-16BL-30N	30 m – 3/8" NPS
PA-16BL-30M	30 m – M16x1,5mm

### **Hadice s 2x ocelovým opletem a koncovkami - 1/4" (NW6) 450 bar**

PA-24BL-10N	10 m - 1/4" NPS
PA-24BL-10M	10 m - M16x1,5mm
PA-24BL-15N	15 m - 1/4" NPS
PA-24BL-15M	15 m - M16x1,5mm
PA-24BL-20N	20 m - 1/4" NPS
PA-24BL-20M	20 m - M16x1,5mm
PA-24BL-25N	25 m - 1/4" NPS
PA-24BL-25M	25 m - M16x1,5mm

### **Hadice s 2x ocelovým opletem a koncovkami - 3/8" (NW10) 450 bar**

PA-26BL-15N	15 m - 3/8" NPS
PA-26BL-15M	15 m - M16x1,5mm
PA-26BL-20N	20 m - 3/8" NPS
PA-26BL-20M	20 m - M16x1,5mm
PA-26BL-25N	25 m - 3/8" NPS
PA-26BL-25M	25 m - M16x1,5mm
PA-26BL-30N	30 m - 3/8" NPS
PA-26BL-30M	30 m - M16x1,5mm

SS – všechny hadice jsou k dispozici s koncovkami v provedení nerez

<https://www.gamin.cz/airless-hadice/>